



THUNDERER

THE DRIVING FORCE

PRODUCT CATALOG

THE MACH SERIES

MACH V

ULTRA HIGH PERFORMANCE

The Thunderer Mach V is an ultra high-performance tire designed for exceptional handling in all weather conditions. On the city streets or on the country roads, the Mach V's asymmetrical tread design and enhanced hydroplaning resistance technology provides superior performance for a quiet, comfortable, and dynamic ride. With 45,000 mile limited treadwear protection and our 25/365 No Questions Asked Limited Protection Policy, the Mach V delivers the quality and value you expect from Thunderer.

45,000 MILES | NO QUESTIONS ASKED

SIZE	LOAD/SPEED	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	UTQG	STOCK#
205/55ZR16 XL	94W	10	24.9	8.4	1477@50	500AA	TH1200
215/55ZR16 XL	97W	10	25.3	8.9	1609@50	500AA	TH1225
205/50ZR17 XL	93W	10	25.1	8.4	1433@50	500AA	TH1205
215/45ZR17 XL	91W	10	24.7	8.4	1356@50	500AA	TH1210
215/55ZR17 XL	98W	10	26.3	8.9	1653@50	500AA	TH1235
225/45ZR17 XL	94W	10	25.0	8.9	1477@50	500AA	TH1240
225/50ZR17 XL	98W	10	25.9	9.2	1653@50	500AA	TH1245
235/50ZR17 XL	100W	10	26.3	9.7	1764@50	500AA	TH1280
225/40ZR18 XL	92W	10	25.1	9.1	1389@50	500AA	TH1260
225/45ZR18 XL	95W	10	25.9	8.9	1521@50	500AA	TH1255
235/45ZR18 XL	98W	10	26.3	9.3	1653@50	500AA	TH1285
245/40ZR18 XL	97W	10	25.7	9.8	1609@50	500AA	TH1305
245/45ZR18 XL	100W	10	26.7	9.6	1764@50	500AA	TH1295
225/35ZR20 XL	90W	10	26.2	9.1	1323@50	500AA	TH1275
245/35ZR20 XL	95W	10	26.8	9.8	1521@50	500AA	TH1315
245/45ZR20 XL	103W	10	28.7	9.6	1929@50	500AA	TH1310
275/35ZR20 XL	102W	10	27.6	10.9	1874@50	500AA	TH1360

108 SIZES

IN 5 PERFORMANCE RADIAL STYLES



MACH IV

R302 | ULTRA HIGH PERFORMANCE

Aggressive yet sophisticated, the Mach IV offers the best of comfort and performance. Designed with Thunderer's unique directional tread pattern, the Mach IV handles aggressive driving and quiet performance. H, V, W rated for proper fitment applications.

60,000 MILES | NO QUESTIONS ASKED

SIZE	LOAD/SPEED	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	UTQG	STOCK#
155/80R13	79H	10	22.80	6.20	965@44	500AA	TH0155
185/55R15	82V	10	23.00	7.60	1050@44	500AA	TH0160
195/50R15	82V	10	22.70	7.90	1050@44	500AA	TH0173
195/55R15	85V	10	23.40	7.90	1140@44	500AA	TH0162
195/60R15	88V	10	24.20	7.90	1230@44	500AA	TH0152
195/65R15	91H	10	25.00	7.90	1355@44	500AA	TH0147
205/55R15	88V	10	23.90	8.40	1230@44	500AA	TH0172
205/60R15	91V	10	24.70	8.20	1355@44	500AA	TH0154
205/65R15	94H	10	25.50	8.20	1480@44	500AA	TH0148
205/70R15	96T	10	26.30	8.20	1565@44	500AA	TH0163
215/60R15	94V	10	25.20	8.70	1480@44	500AA	TH0156
185/55R16	83V	10	24.00	7.60	1070@44	500AA	TH0174
195/50R16 XL	88V	10	23.70	7.90	1230@50	500AA	TH0157
195/55R16	87V	10	24.40	7.90	1200@44	500AA	TH0176
205/55R16	91V	10	24.90	8.40	1355@44	500AA	TH0177
215/55R16 XL	97V	10	25.30	8.90	1609@50	500AA	TH0169
225/50R16	92V	10	24.90	9.20	1390@44	500AA	TH0159
225/55R16 XL	99V	10	25.80	9.20	1710@50	500AA	TH0167
205/50ZR17 XL	93W	10	25.10	8.40	1435@50	420AA	TH0187
215/45ZR17	87W	10	24.70	8.40	1200@44	420AA	TH0188
215/50ZR17	91W	10	25.50	8.90	1355@44	420AA	TH0179
215/55ZR17	94W	10	26.30	8.90	1480@44	420AA	TH0178
215/60R17	96H	10	27.20	8.70	1565@44	500AA	TH0161
225/45ZR17 XL	94W	10	25.00	8.70	1480@50	420AA	TH0181
225/50ZR17	94W	10	25.90	9.20	1480@44	420AA	TH0180
225/40ZR18 XL	92W	10	25.00	9.10	1390@50	420AA	TH0183
225/45ZR18 XL	95W	10	25.90	8.90	1520@50	420AA	TH0182
235/40ZR18 XL	95W	10	25.40	9.50	1520@50	420AA	TH0184
235/35ZR19 XL	91W	10	25.50	9.50	1355@50	420AA	TH0185
265/30ZR19 XL	93W	10	25.30	10.70	1435@50	420AA	TH0186



MACH III

R702 | ULTRA HIGH PERFORMANCE

Aggressive directional tread design offers superior handling in all weather conditions. The solid continuous center rib provides stability at higher speeds and during hard braking. V and W rated for proper fitment applications.

40,000 MILES | NO QUESTIONS ASKED

SIZE	LOAD/SPEED	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	UTQG	STOCK#
205/45ZR16 XL	87W	10	23.2	8.1	1200@50	500AA	TH0131
205/50ZR16	87W	10	24.1	8.4	1200@44	500AA	TH0130
205/40ZR17 XL	84W	10	23.5	8.4	1100@50	500AA	TH0139
205/45ZR17 XL	88W	10	24.3	8.1	1234@50	500AA	TH0132
205/50R17	89V	10	25.1	8.4	1280@44	500AA	TH0136
215/45ZR17	87W	10	24.7	8.4	1200@44	500AA	TH0133
225/55ZR17	97W	10	26.8	9.2	1610@44	500AA	TH0134
235/45ZR17 XL	97W	10	25.4	9.3	1610@50	500AA	TH0137
235/55R17	99H	10	27.2	9.7	1710@44	500AA	TH0135
245/45ZR17 XL	99W	10	25.7	9.6	1710@50	500AA	TH0138
225/45ZR18 XL	95W	10	25.9	8.9	1520@50	500AA	TH0141
235/45ZR18 XL	98W	10	26.3	9.3	1655@50	500AA	TH0143
245/40ZR18 XL	97W	10	25.7	9.8	1610@50	500AA	TH0145
245/45ZR18 XL	100W	10	26.7	9.6	1765@50	500AA	TH0144
235/55R19	101V	10	29.2	9.7	1820@44	500AA	TH0149
225/30ZR20 XL	85W	10	25.4	9.1	1140@50	500AA	TH0151
245/35ZR20 XL	95W	10	26.8	9.8	1520@50	500AA	TH0153
265/50R20 XL	111V	10	30.5	10.9	2405@50	500AA	TH0190



MACH II

R301 | HIGH PERFORMANCE

Great handling performance-rated tire with a split center groove for stability at higher speeds. Mild directional tread pattern offers dependable traction in wet and dry conditions. H or V rated for proper fitment applications.

60,000 MILES | NO QUESTIONS ASKED

SIZE	LOAD/SPEED	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	UTQG	STOCK#
185/55R15	82V	10	23.0	7.6	1047@44	500AA	TH0060
195/50R15	82V	10	22.7	7.9	1047@44	500AA	TH0058
195/55R15	85V	10	23.4	7.9	1135@44	500AA	TH0068
205/55R16	91V	10	24.9	8.4	1356@44	500AA	TH0090
215/55R16 XL	97V	10	25.3	8.9	1609@50	500AA	TH0092
225/55R16	95V	10	25.8	9.2	1521@44	500AA	TH0094



MACH I

R201 | PREMIUM TOURING

Good handling, quiet-running 5-rib design. Long-wearing radial built to last for small and midsize vehicles. T, H and V rated for proper fitment applications.

60,000 MILES | NO QUESTIONS ASKED

SIZE	LOAD/SPEED	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	UTQG	STOCK#
155/80R12	77T	10	21.8	6.2	910@44	500AA	TH0010
165/65R13	77T	10	21.4	6.7	908@44	500AA	TH0011
165/70R13	79T	10	22.1	6.7	963@44	500AA	TH0015
175/70R13	82T	10	22.7	6.7	1047@44	500AA	TH0017
185/70R13	86H	10	23.2	7.4	1168@44	500AA	TH0021
175/65R14	82H	10	23.0	7.0	1047@44	500AA	TH0031
175/70R14	84H	10	23.7	7.0	1102@44	500AA	TH0025
185/60R14	82H	10	22.8	7.4	1047@44	500AA	TH0037
185/65R14	86H	10	23.5	7.4	1168@44	500AA	TH0042
185/70R14	88H	10	24.3	7.4	1234@44	500AA	TH0022
195/60R14	86T	10	23.2	7.9	1160@44	500AA	TH0041
195/70R14	91H	10	24.8	7.9	1356@44	500AA	TH0049
205/70R14 XL	98H	10	25.4	8.2	1655@50	500AA	TH0040
165/80R15	87T	10	25.4	6.5	1200@44	500AA	TH0440
185/60R15	84H	10	23.7	7.4	1100@44	500AA	TH0046
185/65R15	88H	10	24.5	7.4	1234@44	500AA	TH0055
195/60R15	88V	10	24.2	7.9	1234@44	500AA	TH0050
195/65R15	91H	10	25.0	7.9	1355@44	500AA	TH0044
205/60R15	91H	10	24.7	8.2	1355@44	500AA	TH0047
205/65R15	94H	10	25.5	8.2	1480@44	500AA	TH0045
215/60R15	94H	10	25.2	8.7	1480@44	500AA	TH0048
215/65R15	96H	10	26.0	8.7	1565@44	500AA	TH0057
215/70R15	98H	10	26.9	8.7	1655@44	500AA	TH0043
225/60R15	96H	10	25.6	9.0	1565@44	500AA	TH0051
205/55R16	91H	10	24.9	8.4	1355@44	500AA	TH0081
205/60R16	92H	10	25.7	8.2	1390@44	500AA	TH0056
205/65R16	95H	10	26.5	8.2	1520@44	500AA	TH0052
215/60R16	95H	10	26.1	8.7	1520@44	500AA	TH0076
215/65R16 XL	102H	10	27.0	8.7	1875@50	500AA	TH0053
225/60R16	98H	10	26.6	9.0	1655@44	500AA	TH0078
235/60R16	100H	10	27.1	9.5	1765@44	500AA	TH0079
235/65R16	103H	10	28.0	9.5	1930@44	500AA	TH0054
215/55R17	94H	10	26.3	9.0	1480@44	500AA	TH0083
215/65R17	99H	10	28.0	8.7	1710@44	500AA	TH0082
225/50R17	94H	10	25.9	9.2	1480@44	500AA	TH0084

RANGER

A/T

R404 | PREMIUM ALL-TERRAIN

Unique tread design maximizes traction edges for excellent handling on- and off-road. Closed shoulder ensures confident handling in all conditions. Engineered for light truck applications requiring 6 and 10 ply ratings. S and T rated for proper fitments.

SIZE	LOAD/SPEED	PLY	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	UTQG	STOCK#
30x9.50R15LT	104S	6	15	29.5	9.5	1985@50	---	TH0430
30x9.50R15LT OWL	104S	6	15	29.5	9.5	1985@50	---	TH0435
31x10.50R15LT	109S	6	15	30.5	10.5	2270@50	---	TH0450
31x10.50R15LT OWL	109S	6	15	30.5	10.5	2270@50	---	TH0452
235/75R15	105T	-	12	28.9	9.3	2040@44	540AB	TH0610
LT235/75R15	104/101S	6	14	28.9	9.3	1985/1820@50	---	TH0423
LT235/75R15 OWL	104/101S	6	14	28.9	9.3	1985/1820@50	---	TH0427
LT215/85R16	115/112S	10	14	30.4	8.5	2680/2470@80	---	TH0428
LT225/75R16	115/112S	10	14	29.3	8.8	2680/2470@80	---	TH0431
235/70R16	106T	-	12	29.0	9.5	2095@44	540AB	TH0615
LT235/85R16	120/116S	10	15	31.7	9.3	3085/2755@80	---	TH0429
245/70R16 XL	111T	-	12	29.5	9.8	2405@50	540AB	TH0620
245/75R16	111T	-	12	30.5	9.8	2405@44	540AB	TH0611
LT245/75R16	120/116S	10	15	30.5	9.8	3085/2755@80	---	TH0432
LT245/75R16 OWL	120/116S	10	15	30.5	9.8	3085/2755@80	---	TH0624
255/70R16	111T	-	12	30.1	10.2	2405@44	540AB	TH0625
265/70R16	112T	-	12	30.6	10.7	2470@44	540AB	TH0630
265/75R16	116T	-	12	31.7	10.5	2755@44	540AB	TH0612
LT265/75R16	123/120S	10	15	31.7	10.5	3415/3085@80	---	TH0433
LT265/75R16 OWL	123/120S	10	15	31.7	10.5	3415/3085@80	---	TH0626
LT285/75R16	126/123S	10	15	32.8	11.5	3750/3415@80	---	TH0436
LT285/75R16 OWL	126/123S	10	15	32.8	11.5	3750/3415@80	---	TH0627



S/T RATED - STD/XL, 6 & 10 PLY

33 SIZES

COMPLETE SIZE RANGE

15"/20"

SIZE	LOAD/SPEED	PLY	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	UTQG	STOCK#
35x12.50R17LT	121S	10	15	34.5	12.5	3195@65	---	TH0451
LT235/80R17	120/117S	10	15	31.8	9.3	3085/2835@80	---	TH0650
245/65R17	107T	-	12	29.5	9.8	2150@44	540AB	TH0640
245/70R17	110T	-	12	30.6	9.8	2335@44	540AB	TH0631
LT245/75R17	121/118S	10	15	31.5	9.8	3195/2910@80	---	TH0655
265/65R17	112T	-	12	30.6	10.7	2470@44	540AB	TH0645
265/70R17	115T	-	12	31.7	10.7	2680@44	540AB	TH0635
LT265/70R17	121/118S	10	15	31.7	10.7	3195/2910@80	---	TH0434
285/70R17	117T	-	12	32.8	11.5	2835@44	540AB	TH0633
LT285/70R17	121/118S	10	15	32.8	11.5	3195/2910@80	---	TH0437
LT285/70R17 OWL	121/118S	10	15	32.8	11.5	3195/2910@80	---	TH0628
265/60R18	110T	-	12	30.5	10.7	2335@44	540AB	TH0522
265/70R18	116T	-	12	32.6	10.7	2755@44	540AB	TH0517
275/65R18	116T	-	12	32.1	11.0	2755@44	540AB	TH0518
265/50R20	107T	-	12	30.5	10.9	2150@44	540AB	TH0525
275/55R20 XL	117T	-	12	31.9	11.2	2835@50	540AB	TH0521
275/60R20	115T	-	12	33.0	11.0	2680@44	540AB	TH0519
285/55R20	115T	-	12	32.3	11.7	2680@44	540AB	TH0523

RANGER

A/T^R



PREMIUM ALL-TERRAIN

The Ranger A/T^R is Thunderer's next generation of aggressive all-terrain tires designed to kick-start your adventure. With 3D siping technology and rigid interior blocks, the Ranger A/T^R provides unbeatable handling on wet and dry surfaces, while the studdable shoulder lugs and an all new 3PMSF rated tread compound means it handles mud, snow and ice with ease. Carrying an improved 50,000-mile limited treadwear protection and backed by our No Questions Asked, 25/365 Free Replacement Limited Protection Policy on all sizes, the Ranger A/T^R is the ultimate all-terrain tire.

SIZE	LI/SR	LR/PR	TREAD DEPTH	OVERALL DIAMETER	SECTION WIDTH	TSMI#	MAX LOAD @PSI	UTQG	STOCK#
235/75R15	109T	XL	13	28.9	9.3	12	2271@50	500AB	TH1701
LT235/75R15	116/113S	E/10	16	28.9	9.3	15	2756/2535@80	---	TH1723
LT215/85R16	115/112S	E/10	16	30.4	8.5	15	2680/2470@80	---	TH1725
LT225/75R16	115/112S	E/10	16	29.3	8.8	15	2680/2470@80	---	TH1729
235/70R16	109T	XL	13	29.0	9.5	12	2271@50	500AB	TH1707
LT235/85R16	120/116S	E/10	16	31.7	9.3	15	3042/2778@80	---	TH1727
245/75R16	111T	---	13	30.5	9.8	12	2403@44	500AB	TH1703
LT245/75R16	120/116S	E/10	16	30.5	9.8	15	3042/2778@80	---	TH1731
255/70R16	111T	---	13	30.1	10.2	12	2403@44	500AB	TH1709
265/70R16	112T	---	13	30.6	10.7	12	2469@44	500AB	TH1711
265/75R16	116T	---	13	31.7	10.5	12	2756@44	500AB	TH1705
LT265/75R16	123/120S	E/10	16	31.7	10.5	15	3415/3085@80	---	TH1733
LT285/75R16	126/123S	E/10	16	32.8	11.3	15	3748/3417@80	---	TH1735
LT235/80R17	120/117S	E/10	16	31.8	9.3	15	3085/2835@80	---	TH1016
245/65R17	111T	XL	13	29.5	9.8	12	2403@50	500AB	TH1717
245/70R17	110T	---	13	30.6	9.8	12	2337@44	500AB	TH1713
LT245/70R17	119/116S	E/10	16	30.6	9.8	15	3000/2756@80	---	TH1739
LT245/75R17	121/118S	E/10	16	31.5	9.8	15	3197/2910@80	---	TH1737
265/70R17	115T	---	13	31.7	10.7	12	2679@44	500AB	TH1715
LT265/70R17	121/118S	E/10	16	31.7	10.7	15	3197/2910@80	---	TH1741
LT285/70R17	121/118S	E/10	16	32.8	11.5	15	3197/2910@80	---	TH1743
265/60R18	114T	XL	13	30.5	10.7	12	2601@50	500AB	TH1719
265/70R18	116T	---	13	32.6	10.7	12	2756@44	500AB	TH1101
LT265/70R18	124/121S	E/10	16	32.6	10.7	15	3525/3195@80	---	TH1104
275/65R18	116T	XL	13	32.1	11.0	12	2756@50	500AB	TH1106
LT275/65R18	123/120S	E/10	16	32.1	11.0	15	3415/3085@80	---	TH1076
LT275/70R18	125/122S	E/10	16	33.2	11.0	15	3640/3305@80	---	TH1078
LT285/65R18	125/122S	E/10	16	32.6	11.5	15	3640/3305@80	---	TH1013
265/50R20	111T	XL	13	30.5	10.9	12	2405@50	500AB	TH1102
LT265/60R20	121/118S	E/10	16	32.5	10.7	15	3195/2910@80	---	TH1074
275/55R20	117T	XL	13	31.9	11.2	12	2833@50	500AB	TH1721
275/60R20	116T	XL	13	33.0	11.0	12	2756@50	500AB	TH1107
LT275/65R20	126/123S	E/10	16	34.1	11.0	15	3750/3415@80	---	TH1077
LT285/55R20	122/119S	E/10	16	32.4	11.7	15	3305/3000@80	---	TH1108
31x10.50R15LT	109S	C/6	16	30.5	10.6	15	2270@50	---	TH1745
33x12.50R20LT	114S	E/10	16	32.5	12.5	15	2600@65	---	TH1747
35x12.50R20LT	121S	E/10	16	34.5	12.5	15	3195@65	---	TH1749

**RANGER
SERIES**



S/T RATING • STD/XL, 6 & 10 PLY

37

SIZES

COMPLETE SIZE RANGE

15"/20"

TRAC GRIP M/T

R408 | PREMIUM MUD TERRAIN

A maximum-traction on- and off-road radial with an aggressive attitude. The open and tiered tread block elements ensure maximum traction in extreme conditions. Available in 15" through 22" applications to fit today's most popular trucks and SUVs.

The Q-rating along with the 6, 8, 10 & 12 ply rating ensures the necessary load carrying capacity.



SIZE	LOAD/SPEED	PLY	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	STOCK#
30x9.50R15LT	104Q	6	19	29.8	9.5	1985@50	TH2475
31x10.50R15LT	109Q	6	19	30.8	10.6	2270@50	TH2463
32X11.50R15LT	113Q	6	21	31.8	11.4	2535@50	TH2496
33x12.50R15LT*	108Q	6	21	32.8	12.5	2205@35	TH2465
35X12.50R15LT*	113Q	6	21	34.8	12.5	2535@35	TH2498
LT235/75R15	104/101Q	6	19	29.0	9.3	1985/1820@50	TH2467
LT235/85R16*	120/116Q	10	19	32.0	9.3	3085/2755@80	TH2453
LT245/75R16	120/116Q	10	19	30.7	9.8	3085/2755@80	TH2455
LT265/75R16	123/120Q	10	19	31.9	10.5	3415/3085@80	TH2457
LT285/75R16	126/123Q	10	19	33.1	11.3	3750/3415@80	TH2459
LT315/75R16*	121/118Q	8	20	34.8	12.3	3195/2910@50	TH2484
33X12.50R17LT	114Q	8	21	32.8	12.5	2600@50	TH2300
37X12.50R17LT*	124P	8	21	36.8	12.5	3525@50	TH2302
35x12.50R17LT*	121Q	10	21	34.8	12.5	3195@65	TH2466
LT235/80R17	120/117Q	10	20	32.1	9.3	3085/2835@80	TH2486
LT245/75R17	121/118Q	10	19	31.7	9.8	3195/2910@80	TH2471
LT265/70R17	121/118Q	10	19	31.9	10.7	3195/2910@80	TH2461
LT285/70R17*	121/118Q	10	19	33.0	11.5	3195/2910@80	TH2473
LT295/70R17*	121/118Q	10	21	33.5	11.8	3195/2910@80	TH2454
LT315/70R17*	121/118Q	8	20	34.7	12.7	3195/2910@50	TH2488
33x12.50R18LT	122Q	12	21	32.8	12.5	3305@80	TH2500
35x12.50R18LT*	122Q	12	21	34.8	12.5	3305@80	TH2501
LT275/65R18	123/120Q	10	20	32.3	11	3415/3085@80	TH2492
LT275/70R18*	125/122Q	10	19	33.4	11	3640/3305@80	TH2472
LT305/70R18*	126/123Q	10	20	35.1	12.2	3750/3415@65	TH2490
33x12.50R20LT*	119Q	12	21	32.8	12.5	3000@80	TH2502
35x12.50R20LT*	125Q	12	21	34.8	12.5	3640@80	TH2503
37X12.50R20LT*	128Q	12	21	36.8	12.5	3970@80	TH2504
LT305/55R20*	121/118Q	10	20	33.5	12.4	3195/2910@65	TH2494
33X12.50R22LT*	114Q	12	21	32.8	12.5	2600@80	TH2505
35X12.50R22LT*	121Q	12	21	34.8	12.5	3195@80	TH2506
37X13.50R22LT*	128Q	12	21	36.8	13.6	3970@80	TH2507

* 3-Ply Sidewall Construction



RANGER SUV

Quiet, smooth-riding and long-wearing 5 rib design. The tread is angled and siped for all-weather traction. Slotted shoulder tread for confident cornering and handling. Designed for today's trucks, SUVs and CUVs. T, H and V rated for proper fitment and XL rated for proper load carrying capabilities.

SIZE	LI/SR	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	UTQG	STOCK#
205/70R15	96H	11	26.3	8.2	1565@44	560AA	TH0660
215/70R15	98H	11	26.9	8.7	1655@44	560AA	TH0670
225/70R15	100H	11	27.4	9.0	1765@44	560AA	TH0680
215/70R16	100H	11	27.9	8.7	1765@44	560AA	TH0690
225/70R16	103H	11	28.4	9.0	1930@44	560AA	TH0700
235/70R16	106H	11	29.0	9.4	2095@44	560AA	TH0710
245/70R16 XL	111H	11	29.5	9.8	2405@50	560AA	TH0720
265/70R16	112H	11	30.6	10.7	2470@44	560AA	TH0730
265/75R16	116T	11	31.7	10.5	2755@44	560AA	TH0750
225/65R17	102H	11	28.5	9.0	1875@44	560AA	TH0760
235/65R17 XL	108H	11	29.1	9.4	2205@50	560AA	TH0770
235/70R17 XL	111H	11	30.0	9.4	2405@50	560AA	TH0780
245/65R17 XL	111H	11	29.5	9.8	2405@50	560AA	TH0790
245/70R17	110H	11	30.6	9.8	2335@44	560AA	TH0800
265/65R17	112H	11	30.6	10.7	2470@44	560AA	TH0810
265/70R17	115H	11	31.7	10.7	2680@44	560AA	TH0820
235/55R18 XL	104V	11	28.1	9.6	1985@50	560AA	TH0830
255/55R18 XL	109V	11	29.0	10.4	2270@50	560AA	TH0840
265/60R18	110H	11	30.5	10.7	2335@44	560AA	TH0850
265/50R20 XL	112V	11	30.5	10.9	2470@50	560AA	TH0860
275/55R20 XL	117V	11	31.9	11.2	2835@50	560AA	TH0870
285/50R20	112V	11	31.3	11.7	2470@44	560AA	TH0880



COMMERCIAL CLT

Commercial grade light truck tire with multi-ply casing construction to handle heavy work loads. Double steel belted plies provide puncture resistance and durability.

SIZE	LOAD/SPEED	PLY	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	STOCK#
LT235/75R15	116/113Q	10	15	28.9	9.3	2755/2535@80	TH2005
LT215/85R16	115/112Q	10	14	30.4	8.5	2680/2470@80	TH2000
LT225/75R16	115/112Q	10	14	29.3	8.8	2680/2470@80	TH2020
LT235/85R16	120/116Q	10	14	31.7	9.3	3085/2755@80	TH2010
LT245/75R16	120/116Q	10	14	30.5	9.8	3085/2755@80	TH2030
LT265/75R16	123/120Q	10	15	31.7	10.5	3415/3085@80	TH2040
LT245/70R17	119/116Q	10	15	30.6	9.8	3000/2755@80	TH2042
LT245/75R17	121/118Q	10	15	31.5	9.8	3195/2910@80	TH2041
LT265/70R17	121/118Q	10	15	31.7	10.7	3195/2910@80	TH2044
LT275/70R18	125/122Q	10	15	33.2	11.0	3640/3305@80	TH2046



RANGER

R402 | COMMERCIAL

Quiet smooth riding and long wearing with chevron tread design. Engineered for light truck applications requiring 6, 8 & 10 ply rating. Q, R, S and T rated for proper fitment and load carrying capacity.

SIZE	LOAD/SPEED	PLY	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	STOCK#
185/60R15C	94/92T	6	12	23.7	7.4	1480/1390@54	TH0311
195/70R15C	104/102R	8	12	25.8	7.9	1985/1875@65	TH0312
205/70R15C	106/104Q	8	12	26.3	8.2	2094/1984@65	TH0413
215/70R15C	106/104S	8	12	26.9	8.7	2094/1984@55	TH0415
215/70R15C	109/107R	8	12	26.9	8.7	2270/2150@65	TH0416
225/70R15C	112/110R	8	12	27.4	9.0	2470/2335@65	TH0418
195/75R16C	107/105R	8	13	27.5	7.7	2150/2040@69	TH0412
205/65R16C	107/105R	8	12	26.5	8.2	2150/2040@69	TH0424
205/75R16C	110/108R	8	12	28.1	8.0	2335/2205@69	TH0419
215/65R16C	109/107R	8	12	27.0	8.7	2270/2150@69	TH0425
215/75R16C	113/111R	8	12	28.7	8.5	2535/2405@69	TH0421
225/75R16C	116/114R	8	12	29.3	8.8	2755/2600@69	TH0422
235/65R16C	115/113R	8	12	28.0	9.4	2680/2535@69	TH0426
235/65R16C	121/119R	10	12	28.0	9.5	3195/3000@83	TH0410



ST RADIAL

R501 | ST TRAILER RADIAL

Reliable 5 rib design for ST applications. Available in 13" thru 16" in 6, 8, 10 and 12 ply ratings for a wide variety of trailering needs.

SIZE	LOAD/SPEED	PLY	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	STOCK#
ST175/80R13	91/87L	6	9	24.0	7.0	1360/1200@50	TH0480
ST205/75R14	100/96L	6	9	26.1	8.0	1760/1570@50	TH0484
ST205/75R14	105/101L	8	9	26.1	8.0	2040/1820@65	TH0485
ST215/75R14	102/98L	6	9	26.7	8.5	1870/1650@50	TH0486
ST205/75R15	101/97L	6	9	27.1	8.0	1820/1610@50	TH0488
ST205/75R15	107/102L	8	9	27.1	8.0	2150/1870@65	TH0489
ST225/75R15	113/108L	8	9	28.3	8.8	2540/2200@65	TH0490
ST225/75R15	117/112L	10	9	28.3	8.8	2830/2470@80	TH0491
ST235/80R16	123/119L	10	10	30.8	9.3	3420/3000@80	TH0482
ST235/80R16	125/121L	12	10	30.8	9.3	3630/3190@95	TH0483

COMMERCIAL

R102 | COMMERCIAL

SIZE	LOAD/SPEED	PLY	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	STOCK#
195R14C	106/104R	8	11	26.20	7.80	2095/1985@65	TH0314



COMMERCIAL

R200 | COMMERCIAL

The R200 is a speciality load carrying commercial tire in a long-wearing 4-rib commercial design.

SIZE	LOAD/SPEED	PLY	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	STOCK#
155R12C	88/86R	8	10	21.7	6.2	1235/1170@65	TH0500



COMMERCIAL

R101 | COMMERCIAL

The Ranger R101 has a 5-rib tread design engineered to meet the need of specific applications. The R101 is designed to deliver under all conditions.

SIZE	LOAD/SPEED	PLY	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	STOCK#
165R13C	94/92N	8	10	23.5	6.6	1480/1390@65	TH0301
185R14C	102/100Q	8	11	25.6	7.4	1874/1764@65	TH0304
195R14C	106/104P	8	11	26.2	7.8	2094/1984@65	TH0308
205R14C	109/107P	8	11	27.0	8.2	2270/2150@65	TH0309
195R15C	106/104P	8	11	27.2	7.8	2094/1984@65	TH0315
205R16C	110/108R	8	12	29.0	8.2	2335/2205@65	TH0317



COMMERCIAL

R403 | COMMERCIAL

The Ranger R403 has a 5-rib tread design engineered to meet the need of specific applications. The R403 is designed to deliver under all conditions.

SIZE	LOAD/SPEED	PLY	TREAD DEPTH	OUTER DIAMETER	SECTION WIDTH	MAX LOAD @PSI	STOCK#
225/70R15C	109/107S	6	12	27.4	9.0	2270/2150@55	TH0420
245/70R16	107S	4	12	29.5	9.8	2149@44	TH0417



CITY

R202 | COMPACT CAR RADIAL

The CITY R202 is designed with a smooth riding 4-rib tread pattern for economical compact cars.

SIZE	LOAD/SPEED	TREAD DEPTH	OUTER DIAMETER	SIDEWALL	MAX LOAD @PSI	UTQG	STOCK#
155/70R12	73T	9	20.6	6.2	805@44	240AA	TH0002
155/70R13	75T	9	21.6	6.2	853@44	300AB	TH0004
155/80R13	79T	9	22.8	6.2	963@44	300AB	TH0006
165R13	82S	10	23.4	6.5	1047@44	240AA	TH0008

THUNDERER

THE DRIVING FORCE

Thunderer continuously delivers the kind of product your customers want in a replacement tire. High quality with great value, it is a brand you can trust. With our complete lineup of light truck, performance, passenger, trailer and specialty commercial tires, we are ready to help drive your future.



NO QUESTIONS ASKED

25/365 Free Replacement Limited Protection Policy

MARKETING SUPPORT

Intelligent, relevant marketing and point of sale materials that build sales and brand awareness.

JOIN THE DRIVING FORCE

Thunderer tires are distributed exclusively by American-Omni Trading Company through authorized resellers worldwide.

Designed and engineered for North America, Thunderer tires are manufactured in Thailand in state-of-the-art world class factories.

THUNDERER

LIMITED PROTECTION POLICY



***FREE REPLACEMENT**

Every Thunderer tire comes with our No Questions Asked, 25/365 Free Replacement Limited Protection Policy and unbeatable mileage policy (where applicable). The policy fully covers (100% credit) all Thunderer brand passenger, light truck and specialty trailer tires should one become unserviceable due to defective workmanship, materials, or road hazard during the first 25% of useable treadwear or one year from date of purchase, whichever occurs first. For full policy details visit – www.thunderertireusa.com



American Omni Trading Company
1221 Park West Green Drive
Katy, TX 77493
Corporate Phone | 281-600-TIRE
american-omni.com

THUNDERER
THE DRIVING FORCE